

METHOD AND APPARATUS FOR ADJUSTING TIMING
IN A DIGITAL SYSTEM

5

RELATED PATENT APPLICATIONS

METHOD AND APPARATUS FOR PROVIDING DATA FOR SAMPLE

10 RATE CONVERSION having an attorney docket number of
SIG000063 and a filing the date the same as the present
patent application; and

METHOD AND APPARATUS FOR PROVIDING DOMAIN CONVERSIONS
FOR MULTIPLE CHANNELS AND APPLICATIONS THEREOF having an
15 attorney docket number of SIG000059 and a filing the date
the same as the present patent application.

TECHNICAL FIELD OF THE INVENTION

20

This invention relates generally to telecommunications
and more particularly to an analog front-end for use in
such telecommunication systems.

BACKGROUND OF THE INVENTION

25

As is known, data may be communicated from one entity
(e.g. end users, computers, server, facsimile machine et
cetera) to another entity via a communication
30 infrastructure. The communication infrastructure may
include a public switch telephone network (PSTN), the
Internet, wireless communication system, and/or a
combination thereof. Such a communication infrastructure

5

15

30

5

10

15

20

25

30

Figure 5 illustrates a logic diagram of an alternate method for adjusting timing in a digital system in accordance with the present invention.

DETAILED DESCRIPTION OF A PREFERRED EMBODIMENT

Generally, the present invention provides a method and apparatus for adjusting timing in a digital system or telecommunication system. Such a method and apparatus includes processing that begins by dividing a data clock by a 1st value to produce a divided data clock. The processing continues by dividing an analog front-end clock by a 2nd value to produce a divided analog front-end clock. The 1st and 2nd values are selected such that the divided data clock and the divided analog front-end clock have similar clock rates. The processing continues by comparing the phase of the divided data clock with the phase of the divided analog front-end clock to produce a phase difference. The processing continues by adjusting the analog front-end clock based on the phase difference to produce an adjusted analog front-end clock. With such a method and apparatus, the data clock rate of multiple channels derived from the same clock source may be used to synchronize the analog front-end clock.

The present invention can be more fully described with reference to figures 1 through 5. Figure 1 illustrates a schematic block diagram of a multi-channel analog front-end 10. The multi-channel analog front-end 10 includes a sample rate conversion clocking system 12, a plurality of data providing apparatus's 14, 20, 26 and 32, a plurality of sample rate converters 16, 22, 28 and 34, and a plurality of front-end modules 18, 24, 30 and 36. The multi-channel analog front-end 10 supports a plurality of channels (e.g. telecommunication channels, digital system channels, computer data lines, address busses, and/or any

transmission path that includes transmission line characteristics.) As such, the multi-channel analog front-end 10 includes a data providing apparatus, sample rate converter, and analog front-end for each channel that it supports. For example, data providing apparatus 14, sample rate converter 16 and analog front-end 18 supports a 1st channel. As shown, the analog front-end 18 is operably coupled to receive and transmit the bi-directional 1st digital data 44 at the system clock rate (F_{SYS}) and to produce and receive 1st analog data 48 respectively therefrom. Note that the sample rate conversion, the analog front-end processing, and the selection of the 1st sample rate conversion value 46 is further described in co-pending patent application entitled METHOD AND APPARATUS FOR PROVIDING DOMAIN CONVERSIONS FOR MULTIPLE CHANNELS AND APPLICATIONS THEREOF, having an attorney docket number of SIG000059 and a filing date the same as the filing date for the present application.

The data providing apparatus 14 is operably coupled to receive the incoming 1st data 44 at a 1st data rate (F_{D1}) and provides the 1st digital data 44 at the 1st data rate (F_{D1}) to the sample rate converter 16. The sample rate converter 16 based on a 1st sample rate conversion value 46 converts the rate of the 1st data 44 from the 1st data rate (F_{D1}) to a system data rate (F_{SYS}). The system data rate is based on an analog front-end clock 42. Typically, the system clock will be some integer division of the analog front-end clock 42. The determination of the 1st sample rate conversion value 46 and the sample rate conversion performed based on this value is further described in co-pending patent application entitled METHOD AND APPARATUS FOR PROVIDING

DOMAIN CONVERSIONS FOR MULTIPLE CHANNELS AND APPLICATIONS
THEREOF, having an attorney docket number of SIG000059 and
a filing date the same as the filing date for the present
application.

5

A 2nd channel is supported by the data providing
apparatus 20, the sample rate converter 22, and the analog
front-end 24. The data providing apparatus 20 is operably
coupled to receive and transmit the 2nd data 50 and provide
10 it to, and receive it from, the sample rate converter 22 at
a 2nd data rate (F_{D2}). Based on a 2nd sample rate conversion
value 52, the sample rate converter 22 converts the data
rate of the 2nd digital data 50 from the 2nd data rate (F_{D2})
to the system clock rate (F_{SYS}). The analog front-end 24
15 receives the 2nd digital data 50 at the system clock rate
(F_{SYS}) and produces 2nd analog data 54. For incoming 2nd
analog data 54, the sample rate converter 22 converts the
rate of the analog data to the 2nd data rate (F_{D2}).

20

A 3rd channel path is supported by data providing
apparatus 26, the sample rate converter 28, and the analog
front-end 30. The data providing apparatus 26 is operably
coupled to receive and transmit the 3rd digital data 56 and
to provide it to the sample rate converter 28 at a 3rd data
25 rate (F_{D3}). The sample rate converter 28 converts the rate
of the 3rd digital data 56 from the 3rd data rate (F_{D3}) to
the system clock rate (F_{SYS}) based on a 3rd sample rate
conversion value 58. The analog front-end 30 receives the
sample rate converted 3rd digital data and produces 3rd
30 analog data 60 therefrom. For incoming 3rd analog data 60,
the sample rate converter 28 converts the rate of the
analog data to the 3rd data rate (F_{D3}).

A 4th channel is supported by the data providing apparatus 32, the sample rate converter 34, and the analog front-end 36. The data providing apparatus 32 is operably
 5 coupled to process 4th digital data 62 and to provide or receive the 4th digital data at a 4th data rate (F_{D4}). The sample rate converter 34 converts the sample rate of the 4th digital data 62 between the 4th data rate (F_{D4}) and the system clock rate (F_{SYS}) based on a 4th sample rate
 10 conversion value 64. The analog front-end 36 is operably coupled to convert the 4th digital data 62 at the system clock rate to or from 4th analog data 66. For incoming 4th analog data 66, the sample rate converter 34 converts the rate of the analog data to the 4th data rate (F_{D4}).

As one of average skill in the art will appreciate, the multi-channel analog front-end 10 may include more or less channel support devices than depicted in Figure 1. In
 20 addition, the processing by the analog front-end 18, 24, 30 and 36 may include a digital to analog conversion process and/or an analog to digital conversion process. Such that data flow may progress from the digital data 44, 50, 56 and 62 to the analog data 48, 54, 60 and 64, or vice versa.

The sample rate conversion clocking system 12 is operably coupled to a crystal 38, a data clock 40 to produce an analog front-end clock 42. The data clock 40 may correspond to the 1st data clock rate (F_{D1}), the 2nd data
 30 clock rate (F_{D2}), the 3rd data clock rate (F_{D3}), the 4th data clock rate (F_{D4}), and/or an integer division of any of these clocks. Note that in most telecommunication systems, while

the data rates for the 1st, 2nd, 3rd and 4th data 44, 50, 56 and 62 may vary, they will be based on the same backbone clock and be integer multiples or divisions of each other. As such, any one of the clocks may be utilized as the data
 5 clock 40 by the sample rate conversion clocking system 12.

The processing performed by the data providing apparatus 14, 20, 26 and 32 is further described in co-pending patent application entitled METHOD AND APPARATUS
 10 FOR PROVIDING DATA FOR SAMPLE RATE CONVERSION, having an attorney docket number SIG000063 and a filing date the same as the filing date for the present patent application.

Figure 2 illustrates a schematic block diagram of the
 15 sample rate clocking system 12. The sample rate clocking system 12 includes a 1st divider 70, a 2nd divider 72, a phase detector 74, a loop filter 76, a voltage controlled crystal oscillator 78, and an inverter 80. The sample rate conversion clocking system may further include a value
 20 module 90. [With respect to Figure 1, the data providing apparatus 14, 20, 26 and 32 may include processing to perform a physical layer processing which processes data at the data clock rate to produce processed data that is provided to the sample rate converter. The physical layer
 25 processing corresponds to the particular data transmission protocol being utilized. For example, if XDSL data transmission protocol is being utilized, the physical layer receives raw data in the digital domain and adds the XDSL overhead to the data including placing the data in
 30 appropriate frames and providing appropriate frame spacing. Such processing of data is known for such particular types of data transmission protocols.]

The 1st divider 70 is operably coupled to receive a data clock 40 and produce therefrom a divided data clock rate 82. The 1st divider 70 may include a register for storing a 1st divider value and may include a counter to perform a division function, may include a shift register for performing the divider function and/or any other logic circuitry known to divide the rate of a particular clock.

The 2nd divider 72 is operably coupled to receive the analog front-end clock 42 and produce therefrom a divided analog front-end clock 84. The divider 72 may include a register for storing an analog front-end divider clock value, and circuitry for performing the clock division process, such as a counter, shift register, and/or any type of logic circuitry that decimates the rate of a data signal.

The phase detector 74 receives the divided clock rate 82 and the divided analog front-end clock rate 84 to produce a phase difference 86. The divided data clock rate 82 and the divided analog front-end clock rate 84 are of similar rates based on the particular divider values utilized by the 1st divider 70 and the 2nd divider 72. The phase detector 74, which may have a similar construct as a phase detector within a phase locked loop, produces the phase difference 86 to indicate a phase relationship between the divided data clock 82 and the divided analog front-end clock 84.

The loop filter 76 receives the phase difference 86 and produces a control signal 88 therefrom. The control

signal is provided to a voltage control crystal oscillator 78 that regulates the oscillating of crystal 38. The inverter 80 produces a square wave representation of the oscillation of crystal 38, which is representative of the analog front-end clock 42. At the phase difference 86 between the divided data clock rate 82 and divided analog front-end clock 84 vary, the rate of the analog front-end clock 42 varies accordingly. As such, in the closed feedback route system as shown in the sample rate conversion clocking system 12, the analog front-end clock 42 is adjusted to be synchronous with the data clock 40. As one of average skill in the art will appreciate, other means of generating a pullable clock may be used in place of the voltage control crystal oscillator 78. For example, a digitally controlled oscillator may be used that adjusts the capacitance seen by the crystal 38, which causes the clock frequency to change.

The sample rate conversion clocking system 12 may further include a value module 90 that includes a desired sample rate conversion register 92 and a functional module 94. The desired sample rate conversion register 92 stores the desired sample rate conversion rate for the system. Such a sample rate conversion value may correspond to the system clock rate (F_{SYS}). Based on the desired sample rate conversion value, the data clock 40, and the analog front-end clock 42, the functional module 94 produces a sample rate conversion value 96. The sample rate conversion value will be produced for each channel path within the multi-channel analog front-end 10 of Figure 1. The details of determining the sample rate conversion value may be found in co-pending patent application entitled METHOD AND

APPARATUS FOR PROVIDING DOMAIN CONVERSIONS FOR MULTIPLE CHANNELS AND APPLICATIONS THEREOF, having an attorney docket number of SIG000059 and a filing date the same as the filing date for the present application.

5

As one of average skill in the art will appreciate, the sample rate conversion clocking system 12 may be a single system for the entire multi-channel analog front-end 10 or may be separate systems for each channel within the multi-channel analog front-end 10. As such, the sample rate conversion clocking system 12 ensures synchronization between the data clock rates and the analog front-end clock to minimize noise and resulting errors within the multi-channel analog front-end 10.

15

Figure 3 illustrates a schematic block diagram of an apparatus 100 for adjusting timing in a digital system. The apparatus 100 includes a processing module 102 and memory 104. The processing module 102 may be a single memory device or a plurality of memory devices. Such a memory device may be a microprocessor, microcontroller, central processing unit, digital signal processor, state machine, logic circuitry, and/or any device that manipulates signals (analog and/or digital) based on operational instructions. Note than when the processing module implements one or more of its functions via a state machine or logic circuitry, the memory storing the corresponding operational instructions is embedded within the circuitry comprising the state machine and/or logic circuit. The memory 104 may be a single memory device or a plurality of memory devices. Such a memory device may be a read-only memory, random access memory, floppy disk memory,

30

Approved for Release by NSA on 09-08-2013 pursuant to E.O. 13526

system memory, and/or any device that stores digital information. The operational instructions stored in memory 104 and executed by processing module 102 are illustrated in Figures 4 and 5.

5

Figure 4 illustrates a logic diagram of a method for adjusting timing in a digital system. The process begins at Step 110 where a data clock is divided by a 1st value to produce a divided data clock. The 1st value may be
10 determined based on the rate of the data, the particular data transmission protocol being supported by the multi-channel analog front-end, and the system configuration. For example, if the data rate is 70Khz, and the analog front-end clock is 35Mhz, the 1st divider value may be too
15 such that, the divided data clock is 35Khz.

The process then proceeds to Step 112 where the analog front-end clock is divided by a 2nd value to produce a divided analog front-end clock. Continuing with the
20 example in the preceding paragraph, the 2nd value is also based on the rate of the data, the data transport protocol, and the system configuration. In this example, the 2nd value would be 1,000 such that the divided analog front-end clock is 35Khz. The process then proceeds to Step 114
25 where the phase of the divided data clock is compared with the phase of the divided analog front-end clock to produce a phase difference.

The process then proceeds to Step 116 where the analog
30 front-end clock is adjusted based on the phase difference to produce an adjusted analog front-end clock. The processing may continue at Steps 118 where data is received

at the rate of the data clock. The process then proceeds to Step 120 where the rate of the data is converted from the data clock rate to a desired sample conversion rate. The desired sample conversion rate is based on the adjusted

5 analog front-end clock and the data clock. This was previously discussed with reference to Figure 1. The processing then continues at Step 122 where the data is processed by a physical layer at the rate of the data clock to produce processed data. As previously mentioned, the

10 processing at the physical layer places the raw data in frames, and/or packets, and attaches the overhead associated with the particular data transmission protocol with the packetized and/or framed data. The process then proceeds to Step 124 where the rate of the processed data

15 is converted from the data clock rate to the desired clock rate. Note that the desired clock rate corresponds to the system clock rate (F_{SYS}) of Figure 1.

The adjusting of the analog front-end clock may be

20 further described with reference to Steps 126 and 128. At Step 126, the phase difference is filtered to produce a control signal. The process then proceeds to Step 128 where the oscillation of a crystal is controlled based on the control signal. The oscillation of the crystal is used

25 to produce the analog front-end clock. As such, by controlling the oscillation of the crystal, the analog front-end clock is adjusted.

Figure 5 illustrates a logic diagram of an alternate

30 method for adjusting timing in a digital system. The process begins at Step 130 where a data clock rate is sensed. The process then proceeds to Step 132 where an

analog front-end clock rate is sensed. The process then proceeds to Step 134 where a sample rate conversion value is adjusted based on a function of the data clock rate and the analog front-end clock. The particular type of function depends on the desired sample rate conversion value. This is discussed in co-pending patent application entitled METHOD AND APPARATUS FOR PROVIDING DOMAIN CONVERSIONS FOR MULTIPLE CHANNELS AND APPLICATIONS THEREOF, having an attorney docket number of SIG000059 and a filing date the same as the filing date for the present application.

The process then proceeds to Step 136 where a desired sample conversion rate is obtained. The process then proceeds to Step 138 where a functional relationship is established between the data clock rate and the analog front-end clock based on the desired sample conversion rate such that the resultant of the function is the sample rate conversion value. The process then proceeds to Step 140 where the data clock rate is divided by a 1st value to produce a divided data clock. The process then proceeds to Step 142 where the desired sample conversion rate is divided by a 2nd value to produce a divided sample conversion rate. The process then proceeds to Step 144 where the phase of the divided data clock is compared with the phase of the divided sample conversion rate to produce a phase difference. The process then proceeds to Step 146 where the analog front-end clock rate is adjusted based on the phase difference to produce an adjusted analog front-end clock.

The process then proceeds to Step 148 where data is received at a data clock rate. The process then proceeds to Step 150 where the rate of the data is converted from the data clock rate to the desired sample conversion rate.

- 5 The process then proceeds to Step 152 where the data is processed by a physical layer at the rate of the data clock to produce processed data. The process then proceeds to Step 154 where the rate of the processed data is converted from the data clock rate to the desired clock rate (e.g.
- 10 the system clock (F_{SYS})).

- The preceding discussion has presented a method and apparatus for adjusting timing in multi-channel analog front-end. By controlling the timing, noise between the
- 15 circuitries that support the multi-channels is reduced. As such, a more efficient multi-channel analog front-end is obtained. As one of average skill in the art will appreciate, other embodiments may be derived from the teaching of the present invention without deviating from
- 20 the scope.